
## EKF 523 N T UD







## ELECTRIC COMBIOVEN WITH TOUCH SCREEN

The latest 5 trays 2/3 GN with just 55cm width size , EKF523NTUD establishes a new benchmark level for cafes and convenience store thanks to its compact size, a truly intelligent design along with technological solutions such as integrated LED door light, capacitive touch panel, customizable programs, black or white background theme change, steam injection, inner drain.







| DIMENSIONAL FEATURES             |     |     |     |
|----------------------------------|-----|-----|-----|
| Oven dimensions (WxDxH mm)       | 550 | 754 | 662 |
| Oven weight (kg)                 | 40  |     |     |
| Distance between rack rails (mm) | 80  |     |     |

| ELECTRICAL FEATURES      |                 |
|--------------------------|-----------------|
| Power supply (kW)        | 3,2             |
| Frequency (Hz)           | 50/60           |
| Voltage (Volt)           | AC 220/230      |
| N° of motors             | 1 Bidirectional |
| Boiler                   | /               |
| Protection against water | IPX4            |

| FUNCTIONAL FEATURES        |  |  |  |
|----------------------------|--|--|--|
| Power                      | Electricity  |  |  |
| Capacity                   | N° 5 Trays / grids 2/3 GN<br>(354x325 mm)                        |  |  |
| Type of cooking            | Ventilated   |  |  |
| Steam                      | Direct steam injection with manual<br>% setup (from 10% to 100%) |  |  |
| Cooking chamber            | AISI 304 Stainless Steel   |  |  |
| Temperature                | 30 - 270 °C  |  |  |
| Temperature control        | Digital probe  |  |  |
| Control panel              | Touch screen-right side  |  |  |
| N° of programs             | 100  |  |  |
| Programmable cooking steps | 5  |  |  |
| Pre-heating temperature    | 180 °C   |  |  |
| Programmable oven start    | Available  |  |  |
| Pre-heating function       | Available  |  |  |
| Door                       | Right side opening<br>Ventilated<br>Inspectionable glass         |  |  |
| Modularity                 | /  |  |  |

| 599                               | 784        | 735                                      |  |  |  |
|-----------------------------------|------------|--|--|--|--|
| 1 dx + 1 sx                       |            |  |  |  |  |
| Single-Phase [3G 1,5] - L=1600 mm |            |  |  |  |  |
| One on the oven                   |            |  |  |  |  |
| Manual washing set up             |            |  |  |  |  |
| Core probe predisposition         |            |  |  |  |  |
| Condensation hood predisposition  |            |  |  |  |  |
|                                   |            |  |  |  |  |
|                                   | Single-Pha | 1 dx + 1 sx<br>Single-Phase [3G 1,5] - I |  |  |  |



Servicing NSW and ACT

PLUS

Core probe (on request) Core probe support (on request)

> Ph: 02 4879 3808 www.briquip.com.au admin@briquip.com.au