

4 TROLLEY HIGH-CAPACITY INDUSTRIAL DEHYDRATOR

INDUSTRIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL




Save Set Recipes



CSV Data Export



Completion Cooling Cycle



Uniform Drying Without Rotation



Programmable Staged Drying



DrySync™ Technology



Remote Operational Control



Food-Grade 304 Stainless Steel

MODEL IU04 SPECIFICATIONS

| | | | |
|-------------------------------|--|------------------------|----------------------------|
| Max Power Rating | 27.25 kW | Internal Airflow | 13600 m ³ /hr |
| Avg. Power Rating | 12-14 kW | Number of Exhaust Fans | 2 |
| Voltage / Frequency | 3-Phase / 50-60Hz - 400V, Custom | Total Trolleys | 4 Trolley |
| Product Dimension (W x H x D) | 2200 x 2000 x 2200 mm | Trolley Dimensions | 920 x 1450 x 695 mm |
| Loading Footprint Required | 2200 x 2000 x 3600 mm | Space Between Trays | 40 - 80 mm |
| Machine Weight | 1100 kg | Total Trays | 120 - 240 trays |
| Temperature Range | Ambient - 120°C | Tray Dimensions | 460 x 640 mm |
| Exhaust Air Volume | 850 m ³ /hr (per Exhaust Fan) | Total Tray Area | 35.3 - 70.7 m ² |
| Static Pressure Rating | 1020 pa (per Exhaust Fan) | Timer | 0 - 5000 hours |
| Product Material | Double walled industrial-grade 304 stainless steel. Insulated with high density aluminium silicate cotton. | | |