

Technical information

Polar 2-95



Characteristics

- Supplied with two sealing bars as standard (front/rear)
- Optional at no extra cost: Two sealing bars (left/right)
- Double seal as standard (two sealing wires).
Optional at no extra cost: Cut-off seal/Wide seal (10 mm)
- Easy-to-remove silicone holders for easy cleaning
- Digital time control with ten-program memory as standard
- Soft Air as standard to protect the product and vacuum bag
- Stainless steel casing and flat working plate
- Supplied with eight insert plates for a faster cycle and good product positioning
- IP-65 classification

Opties

- Three sealing bars (front/middle/rear)
- 1-2 Cut-off seal/Bi-Active seal
- Sensor control
- Advanced Control System (ACS)
- Liquid control
- Gas flush (incl. compressed air connection)
- Connection for external pump
- Extra sealing capacity
- (Lightweight) bag clamp
- Automatic lid (automatic or with foot pedal)

Accessories

- Thermal label printer (only in combination with ACS)
- Inclined insert plate (for liquids and powders)
- Maintenance set for standard maintenance



Specs	Polar 2-95	
Chamber LxWxH (mm)	730x1100x280	
Machine LxWxH (mm)	1215x2420x1595	
Voltage	400V-3-50Hz 230V-3-50Hz 220V-3-60Hz 200V-3-50/60Hz	
Pump capacity 50 Hz/60 Hz (m3)	300 / 360	
Machine cycle 50 Hz/60 Hz (sec.)	14 - 31 / 12 - 27	
Power (kW)	5,5 - 7,8	
Weight (kg)	767	
Net seal length (mm)	2 x 1090 - standard - option 2 x 828 - option 3 x 1090	
Sealing bar configuration	standard	option
- standard		
- option		
- option		

Dimensions mm

